

## KANPE LEAD & CHROMATE FREE PRIMER

**DESCRIPTION** An alkyd based primer with special grade of anti-corrosive pigment as rust inhibitor.  
**Certified to Singapore Standard (SS494:2001).**

**USES** As a primer for steel. Designed to protect both indoor & outdoor structures.

**CHARACTERISTICS**

- Tough film
- Excellent adhesion to substrate
- Excellent adhesion to subsequent coats
- Good anti-corrosive properties
- Good moisture resistances
- Easy application

### APPLICATION DATA

**METHOD OF APPLICATION** Airless spray, Brush, Roller

**PAINT DILUTION** Product is ready for use. If thinning is required, max. 10% using Paint Thinner A.

**PRACTICAL COVERAGE** 9 m<sup>2</sup> / Ltr / coat (standard)

**DRYING TIME**  
Touch Dry : 30 mins at 30°C  
Hard Dry : 6 hrs at 30°C

**OVERCOATING INTERVAL** Min. 16 hrs at 30°C

**STORAGE** Replace lid cover after each use. Remaining paint must be stored in cool, dry and clean place.

### GENERAL INFORMATION

**COLOUR** Grey

**SPECIFIC GRAVITY** 1.19 g / cm<sup>3</sup>

**PACKING SIZE** 5 Ltrs

**RECOMMENDED OVERCOAT** Unilux Undercoat For Gloss Enamel (SS34:1998)