

SUPER UNILIC ALGAE RESISTANT EMULSION

DESCRIPTION An acrylic emulsion paint with excellent resistance to algae and fungus growth.
Certified to Singapore Standard (SS345:1990)

USES As a decorative & protective finish of various building surfaces:

- Concrete
- Plaster
- Brickwork
- Hard & Soft Board

CHARACTERISTICS

- Excellent algae & fungus resistance
- Excellent durability
- Excellent colour retention
- Excellent adhesion
- Excellent scrub resistance
- Easy application
- High opacity for good coverage

APPLICATION DATA

METHOD OF APPLICATION Airless spray, Brush, Roller

PAINT DILUTION Product is ready for use. If thinning is required, max. 10% using fresh water.

PRACTICAL COVERAGE 10 m² / Ltr / coat (standard)

DRYING TIME 30 mins at 30°C

OVERCOATING INTERVAL Min. 2 hrs at 30°C

STORAGE Replace lid cover after each use. Remaining paint must be stored in cool, dry and clean place.

GENERAL INFORMATION

SPECIFIC GRAVITY 1.25 g / cm³

PACKING SIZE 20 Ltrs

RECOMMENDED SEALER Hi Sealer Water Base, Oil Base Sealer No.3, AP Sealer