

# UNILUX ALUMINIUM WOOD PRIMER

DESCRIPTION	An effective alkyd modified resin with leafing aluminum pigment. <b>Certified to Singapore Standard (SS:38-Type 1:1998).</b>
USES	As a primer for wooden substrates.
CHARACTERISTICS	<ul style="list-style-type: none"> <li>• Good sealing properties</li> <li>• No added lead components</li> <li>• Excellent adhesion to substrate</li> <li>• Excellent adhesion to subsequent coats</li> <li>• Excellent water resistance</li> <li>• Good workability</li> <li>• Less smell</li> </ul>
<b>APPLICATION DATA</b>	
METHOD OF APPLICATION	Airless spray, Brush, Roller
PAINT DILUTION	Product is ready for use. If thinning is required, max. 10% using Paint Thinner A.
PRACTICAL COVERAGE	9 m <sup>2</sup> / Ltr / coat (standard)
DRYING TIME	Touch Dry : 1 hr at 30°C Hard Dry : 3 hrs at 30°C
OVERCOATING INTERVAL	Min. 10 hrs at 30°C
STORAGE	Replace lid cover after each use. Remaining paint must be stored in cool, dry and clean place.
<b>GENERAL INFORMATION</b>	
COLOUR	Silver
SPECIFIC GRAVITY	0.95 g / cm <sup>3</sup>
PACKING SIZE	5 Ltrs
RECOMMENDED OVERCOAT	Unilux Undercoat For Gloss Enamel (SS34:1998)