

UNILUX GLOSS ENAMEL FINISHING

DESCRIPTION	A versatile long oil alkyd resin-based paint which cures by air oxidation. Certified to Singapore Standard (SS7:1998).
USES	As a decorative paint for primed wooden and metal surfaces for both interior and exterior: <ul style="list-style-type: none"> • Kiln dry timber • Plywood • Ferrous metals • Non-ferrous metals
CHARACTERISTICS	<ul style="list-style-type: none"> • No added lead components • Excellent hiding properties • Excellent weathering resistance • Excellent washability with mild detergent • High gloss
APPLICATION DATA	
METHOD OF APPLICATION	Airless spray, Brush, Roller
PAINT DILUTION	Product is ready for use. If thinning is required, max. 10% using Paint Thinner A.
PRACTICAL COVERAGE	10 m ² / Ltr / coat (standard)
DRYING TIME	Touch Dry: 3 hrs at 30°C Hard Dry : 8 hrs at 30°C
OVERCOATING INTERVAL	Min. 10 hrs at 30°C
STORAGE	Replace lid cover after each use. Remaining paint must be stored in cool, dry and clean place.
GENERAL INFORMATION	
SPECIFIC GRAVITY	1.12 g / cm ³ (White)
PACKING SIZE	5 Ltrs
RECOMMENDED UNDERCOAT	Unilux Undercoat for Gloss Enamel (SS34:1998)