

# UNILUX UNDERCOAT FOR GLOSS ENAMEL

**DESCRIPTION** A versatile long oil alkyd resin based paint which cures by air oxidation. **Certified to Singapore Standard (SS34:1998).**

**USES** As an intermediate coat for exterior and interior use. Suitable for primed metallic and wooden substrates.

**CHARACTERISTICS**

- No added lead components
- Excellent adhesion over rust prohibitive coating
- Tough film
- Provide excellent base for finishing coat
- Easy application

## APPLICATION DATA

**METHOD OF APPLICATION** Airless spray, Brush, Roller

**PAINT DILUTION** Product is ready for use. If thinning is required, max. 10% using Paint Thinner A.

**PRACTICAL COVERAGE** 13 m<sup>2</sup> / Ltr / coat (standard)

**DRYING TIME** Touch Dry: 30 mins at 30°C  
Hard Dry : 6 hrs at 30°C

**OVERCOATING INTERVAL** Min. 10 hrs at 30°C

**STORAGE** Replace lid cover after each use. Remaining paint must be stored in cool, dry and clean place.

## GENERAL INFORMATION

**COLOUR** White

**SPECIFIC GRAVITY** 1.48 g / cm<sup>3</sup>

**PACKING SIZE** 5 Ltrs

**RECOMMENDED PRIMER COAT** Wood Unilux Aluminum Wood Primer (SS:38-Type 1:1998)  
Steel Kanpe Lead & Chromate Free Primer (SS494:2001)

**RECOMMENDED OVERCOAT** Unilux Gloss Enamel Finishing (SS7:1998)